

MAXHUB

Product Spec

1. Product appearance



2. Interface

USB2.0	1
--------	---

3. Function

Maximum number of connections	1 USB receiver can connect to 8 transmitters at the same time
Maximum connection distance	12m
Operating Systems Supported	Windows7/8/8.1/10; mac OS 10.10~10.13
Operating frequency	2.4GHz, 5GHz

MAXHUB

Transmission Delay	The minimum delay in the laboratory environment is 90ms (the actual situation is affected by the use environment)
Frame rate	Windows7: 1920x1080@20fps/1366x768@20fps Windows8(8.1)/OSX: 1920x1080@30fps/1366x768@30fps Windows10: 1920x1080@30fps/1366x768@30fps

4. Power

Power Requirements	5V DC
Power Consumption	0.85W

5. Physical Specification

Button	1pcs
Dimension L × H × W	178.7 × 77 × 21.3mm
Dimension(package) L × W × H	210 × 111 × 44mm
Net Weight	0.1kg
Gross Weight	0.25kg

MAXHUB

6. Accessory

User Manual	1pcs
-------------	------

7. Environmental Condition

Operation Temperature	0°C–40°C
Operation Humidity	10% – 90%RH
Storage Temperature	–20°C –60°C
Storage Humidity	10% – 90%RH

8. Statement

Size and weight vary by configuration and manufacturing process, please refer to the actual product.

The product images are for illustrative purposes only and may slightly differ in appearance, colour, size, etc. from the actual product.

The description, illustrations, etc. in this document may subject to change in accordance with the latest product specification and performance.

Should the above-mentioned change in the document become necessary, the document may be updated without written notice.